

StepHero

# Smart Contract Audit Report





## **TABLE OF CONTENTS**

#### | Audited Details

- Audited Project
- Blockchain
- Addresses
- Project Website
- Codebase

#### Summary

- Contract Summary
- Audit Findings Summary
- Vulnerabilities Summary

#### Conclusion

#### | Audit Results

#### Smart Contract Analysis

- Detected Vulnerabilities

### Disclaimer

#### About Us



## **AUDITED DETAILS**

## Audited Project

Project name	Token ticker	Blockchain	
StepHero	StepHero	Binance Smart Chain	

## Addresses

Contract address	0xe8176d414560cfe1bf82fd73b986823b89e4f545	
Contract deployer address	0x5042FEe60DaDA84d252dc0301Fd04Cc2891DeAC8	

## Project Website

https://www.stephero.io/

## Codebase

https://bscscan.com/address/0xe8176d414560cfe1bf82fd73b986823b89e4f545#contracts



## **SUMMARY**

Step Hero Multiverse is the one-stop shop for P2E gamers, which brings you extraordinary gaming experiences & lucrative earning opportunities. We provide an NFT gaming ecosystem with HERO Game Hub, which gathers a series of attractive blockchain games with accompanying features such as NFT marketplace, NFT farming, Summon Gate, and NFT lending (coming soon). The ecosystem has a unified P2E economy centered on \$STEP and \$HERO tokens. These are the two primary tokens used in the ecosystem as payment and reward currencies. All games in Step Hero Multiverse use the same native token (\$HERO) and in-game token (\$STEP). Our vision is to become an ecosystem with millions of users benefiting and monetizing it daily. Our mission is to bring sustainable earning opportunities for those who love NFT gaming and, through that, popularize the application of blockchain technology.

### Contract Summary

#### **Documentation Quality**

StepHero provides a very good documentation with standard of solidity base code.

• The technical description is provided clearly and structured and also dont have any high risk issue.

#### **Code Quality**

The Overall quality of the basecode is standard.

• Standard solidity basecode and rules are already followed by StepHero with the discovery of several low issues.

#### **Test Coverage**

Test coverage of the project is 100% (Through Codebase)

### Audit Findings Summary

- SWC-103 | Pragma statements can be allowed to float when a contract is intended on lines 11, 95, 123, 149, 504 and 576.
- SWC-116 | It is recommended to use oracles for block values as a proxy for time on lines 601 and 601.



## CONCLUSION

We have audited the StepHero project released on September 2021 to discover issues and identify potential security vulnerabilities in StepHero Project. This process is used to find technical issues and security loopholes which might be found in the smart contract.

The security audit report provides a satisfactory result with some low-risk issues.

The issues found in the StepHero smart contract code do not pose a considerable risk. The writing of the contract is close to the standard of writing contracts in general. The low-risk issues found are some a floating pragma is set, and a control flow decision is made based on The block.timestamp environment variable. The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code. The block.timestamp environment variable is used to determine a control flow decision. Note that the values of variables like coinbase, gaslimit, block number, and timestamp are predictable and can be manipulated by a malicious miner. Also, keep in mind that attackers know hashes of earlier blocks. Don't use any of those environment variables as sources of randomness and be aware that the use of these variables introduces a certain level of trust into miners.



# **AUDIT RESULT**

Article	Category	Description	Result	
Default Visibility	SWC-100 SWC-108	Functions and state variables visibility should be set explicitly. Visibility levels should be specified consciously.		
Integer Overflow and Underflow	SWC-101	If unchecked math is used, all math operations should be safe from overflows and underflows.	PASS	
Outdated Compiler Version	SWC-102	It is recommended to use a recent version of the Solidity compiler.	PASS	
Floating Pragma	SWC-103	Contracts should be deployed with the same compiler version and flags that they have been tested thoroughly.		
Unchecked Call Return Value	SWC-104	The return value of a message call should be checked.	PASS	
Unprotected Ether Withdrawal	SWC-105	Due to missing or insufficient access controls, malicious parties can withdraw from the contract.	PASS	
SELFDESTRUCT Instruction	SWC-106	The contract should not be self-destructible while it has funds belonging to users.	PASS	
Reentrancy	SWC-107	Check effect interaction pattern should be followed if the code performs recursive call.	PASS	
Uninitialized Storage Pointer	SWC-109	Uninitialized local storage variables can point to unexpected storage locations in the contract.	PASS	
Assert Violation	SWC-110 SWC-123	Properly functioning code should never reach a failing assert statement.		
Deprecated Solidity Functions	SWC-111	Deprecated built-in functions should never be used.	PASS	
Delegate call to Untrusted Callee	SWC-112	Delegatecalls should only be allowed to trusted addresses.	PASS	



DoS (Denial of Service)	SWC-113 SWC-128	Execution of the code should never be blocked by a specific contract state unless required.	PASS	
Race Conditions	SWC-114	Race Conditions and Transactions Order Dependency should not be possible.		
Authorization through tx.origin	SWC-115	tx.origin should not be used for authorization.	PASS	
Block values as a proxy for time	SWC-116	Block numbers should not be used for time calculations.		
Signature Unique ID	SWC-117 SWC-121 SWC-122	Signed messages should always have a unique id. A transaction hash should not be used as a unique id.		
Incorrect Constructor Name	SWC-118	Constructors are special functions that are called only once during the contract creation.		
Shadowing State Variable	SWC-119	State variables should not be shadowed.		
Weak Sources of Randomness	SWC-120	Random values should never be generated from Chain Attributes or be predictable.	in PASS	
Write to Arbitrary Storage Location	SWC-124	The contract is responsible for ensuring that only authorized user or contract accounts may write to sensitive storage locations.		
Incorrect Inheritance Order	SWC-125	When inheriting multiple contracts, especially if they have identical functions, a developer should carefully specify inheritance in the correct order. The rule of thumb is to inherit contracts from more /general/ to more /specific/.	PASS	
Insufficient Gas Griefing	SWC-126	Insufficient gas griefing attacks can be performed on contracts which accept data and use it in a sub-call on another contract.		
Arbitrary Jump Function	SWC-127	As Solidity doesnt support pointer arithmetics, it is impossible to change such variable to an arbitrary value.		



Typographical Error	SWC-129	A typographical error can occur for example when the intent of a defined operation is to sum a number to a variable.		
Override control character	SWC-130	Malicious actors can use the Right-To-Left-Override unicode character to force RTL text rendering and confuse users as to the real intent of a contract.		
Unused variables	SWC-131 SWC-135	Unused variables are allowed in Solidity and they do not pose a direct security issue.		
Unexpected Ether balance	SWC-132	Contracts can behave erroneously when they strictly assume a specific Ether balance.		
Hash Collisions Variable	SWC-133	Using abi.encodePacked() with multiple variable length arguments can, in certain situations, lead to a hash collision.		
Hardcoded gas amount	SWC-134	The transfer() and send() functions forward a fixed amount of 2300 gas.		
Unencrypted Private Data	SWC-136	It is a common misconception that private type variables cannot be read.	PASS	



## **SMART CONTRACT ANALYSIS**

Started	Wednesday Sep 15 2021 06:55:41 GMT+0000 (Coordinated Universal Time)
Finished	Thursday Sep 16 2021 17:56:51 GMT+0000 (Coordinated Universal Time)
Mode	Standard
Main Source File	StepHero.sol

## Detected Issues

ID	Title	Severity	Status
SWC-103	A FLOATING PRAGMA IS SET.	low	acknowledged
SWC-103	A FLOATING PRAGMA IS SET.	low	acknowledged
SWC-103	A FLOATING PRAGMA IS SET.	low	acknowledged
SWC-103	A FLOATING PRAGMA IS SET.	low	acknowledged
SWC-103	A FLOATING PRAGMA IS SET.	low	acknowledged
SWC-103	A FLOATING PRAGMA IS SET.	low	acknowledged
SWC-116	A CONTROL FLOW DECISION IS MADE BASED ON THE BLOCK.TIMESTAMP ENVIRONMENT VARIABLE.	low	acknowledged
SWC-116	A CONTROL FLOW DECISION IS MADE BASED ON THE BLOCK.TIMESTAMP ENVIRONMENT VARIABLE.	low	acknowledged



LINE 11

#### **low SEVERITY**

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

#### Source File

- StepHero.sol

```
10
11 pragma solidity ^0.8.0;
12
13 /**
14 * @dev Interface of the ERC20 standard as defined in the EIP.
15
```



LINE 95

#### **low SEVERITY**

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

#### Source File

- StepHero.sol

```
94
95 pragma solidity ^0.8.0;
96
97 /**
98 * @dev Interface for the optional metadata functions from the ERC20 standard.
99
```



**LINE 123** 

#### **low SEVERITY**

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

#### Source File

- StepHero.sol

```
122
123 pragma solidity ^0.8.0;
124
125 /*
126 * @dev Provides information about the current execution context, including the
127
```



**LINE** 149

#### **low SEVERITY**

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

#### Source File

- StepHero.sol

```
148
149 pragma solidity ^0.8.0;
150
151
152
153
```



**LINE 504** 

#### **low SEVERITY**

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

#### Source File

- StepHero.sol

```
503
504 pragma solidity ^0.8.0;
505
506 /**
507 * @dev Contract module which provides a basic access control mechanism, where
508
```



**LINE 576** 

#### **low SEVERITY**

The current pragma Solidity directive is ""^0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

#### Source File

- StepHero.sol

```
575
576 pragma solidity ^0.8.0;
577
578
579 contract StepHero is ERC20, Ownable {
580
```



# SWC-116 | A CONTROL FLOW DECISION IS MADE BASED ON THE BLOCK.TIMESTAMP ENVIRONMENT VARIABLE.

**LINE 601** 

#### **low SEVERITY**

The block timestamp environment variable is used to determine a control flow decision. Note that the values of variables like coinbase, gaslimit, block number and timestamp are predictable and can be manipulated by a malicious miner. Also keep in mind that attackers know hashes of earlier blocks. Don't use any of those environment variables as sources of randomness and be aware that use of these variables introduces a certain level of trust into miners.

#### Source File

- StepHero.sol

```
function transfer(address recipient, uint256 amount) public virtual override
returns (bool) {
  if (block.timestamp >= startTime && block.timestamp <= endTime) {
    require(whitelist[recipient], 'StepHero: not in whitelist');
  }
  }
  604
  605</pre>
```



# SWC-116 | A CONTROL FLOW DECISION IS MADE BASED ON THE BLOCK.TIMESTAMP ENVIRONMENT VARIABLE.

**LINE 601** 

#### **low SEVERITY**

The block timestamp environment variable is used to determine a control flow decision. Note that the values of variables like coinbase, gaslimit, block number and timestamp are predictable and can be manipulated by a malicious miner. Also keep in mind that attackers know hashes of earlier blocks. Don't use any of those environment variables as sources of randomness and be aware that use of these variables introduces a certain level of trust into miners.

#### Source File

- StepHero.sol

```
function transfer(address recipient, uint256 amount) public virtual override
returns (bool) {
  if (block.timestamp >= startTime && block.timestamp <= endTime) {
    require(whitelist[recipient], 'StepHero: not in whitelist');
  }
  }
  604
  605</pre>
```



## **DISCLAIMER**

This report is subject to the terms and conditions (including without limitation, description of services, confidentiality, disclaimer and limitation of liability) set forth in the Services Agreement, or the scope of services, and terms and conditions provided to you ("Customer" or the "Company") in connection with the Agreement. This report provided in connection with the Services set forth in the Agreement shall be used by the Company only to the extent permitted under the terms and conditions set forth in the Agreement. This report may not be transmitted, disclosed, referred to, or relied upon by any person for any purposes, nor may copies be delivered to any other person other than the Company, without Sysfixed's prior written consent in each instance.

This report is not, nor should be considered, an "endorsement" or "disapproval" of any particular project or team. This report is not, nor should be considered, an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Sysfixed to perform a security assessment. This report does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors, business, business model, or legal compliance.

This is a limited report on our findings based on our analysis, in accordance with good industry practice as of the date of this report, in relation to cybersecurity vulnerabilities and issues in the framework and algorithms based on smart contracts, the details of which are set out in this report. In order to get a full view of our analysis, it is crucial for you to read the full report. While we have done our best in conducting our analysis and producing this report, it is important to note that you should not rely on this report and cannot claim against us on the basis of what it says or doesn't say, or how we produced it, and it is important for you to conduct your own independent investigations before making any decisions. We go into more detail on this in the below disclaimer below – please make sure to read it in full.

This report should not be used in any way to make decisions around investment or involvement with any particular project. This report in no way provides investment advice, nor should be leveraged as investment advice of any sort. This report represents an extensive assessing process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

This report is provided for information purposes only and on a non-reliance basis and does not constitute investment advice. No one shall have any right to rely on the report or its contents, and Sysfixed and its affiliates (including holding companies, shareholders, subsidiaries, employees, directors, officers, and other representatives) (Sysfixed) owe no duty of care.



## **ABOUT US**

Sysfixed is a blockchain security certification organization established in 2021 with the objective to provide smart contract security services and verify their correctness in blockchain-based protocols. Sysfixed automatically scans for security vulnerabilities in Ethereum and other EVM-based blockchain smart contracts. Sysfixed a comprehensive range of analysis techniques—including static analysis, dynamic analysis, and symbolic execution—can accurately detect security vulnerabilities to provide an in-depth analysis report. With a vibrant ecosystem of world-class integration partners that amplify developer productivity, Sysfixed can be utilized in all phases of your project's lifecycle. Our team of security experts is dedicated to the research and improvement of our tools and techniques used to fortify your code.