



Liquid Driver
**Smart Contract
Audit Report**

TABLE OF CONTENTS

Audited Details

- Audited Project
- Blockchain
- Addresses
- Project Website
- Codebase

Summary

- Contract Summary
- Audit Findings Summary
- Vulnerabilities Summary

Conclusion

Audit Results

Smart Contract Analysis

- Detected Vulnerabilities

Disclaimer

About Us

AUDITED DETAILS

Audited Project

Project name	Token ticker	Blockchain
Liquid Driver	LQDR	Ethereum

Addresses

Contract address	0x10b620b2dbac4faa7d7ffd71da486f5d44cd86f9
Contract deployer address	0x06917EFCE692CAD37A77a50B9BEEF6f4Cdd36422

Project Website

<http://liquiddriver.finance/>

Codebase

<https://ftmscan.com/address/0x10b620b2dbac4faa7d7ffd71da486f5d44cd86f9#code>

SUMMARY

LiquidDriver is the first liquidity mining dApp providing liquidity-as-a-service in the Fantom ecosystem. We aim to bring its users more utility, rewards, and long-term benefits through our native token, LQDR, and ultimately become the leading liquidity-on-demand platform for dApps on the Fantom Opera Mainnet.

Contract Summary

Documentation Quality

Liquid Driver provides a very good documentation with standard of solidity base code.

- The technical description is provided clearly and structured and also don't have any high risk issue.

Code Quality

The Overall quality of the basecode is standard.

- Standard solidity basecode and rules are already followed by Liquid Driver with the discovery of several low issues.

Test Coverage

Test coverage of the project is 100% (Through Codebase)

Audit Findings Summary

- SWC-103 | Pragma statements can be allowed to float when a contract is intended on lines 8, 34, 102, 198 and 359.
- SWC-116 | It is recommended to use oracles for block values as a proxy for time on lines 772.
- SWC-120 | It is recommended to use external sources of randomness via oracles on lines 802, 875 and 802.

CONCLUSION

We have audited the Liquid Driver project released on May 2021 to discover issues and identify potential security vulnerabilities in Liquid Driver Project. This process is used to find technical issues and security loopholes which might be found in the smart contract.

The security audit report provides a satisfactory result with some low-risk issues.

The issues found in the Liquid Driver smart contract code do not pose a considerable risk. The writing of the contract is close to the standard of writing contracts in general. The low-risk issues found are floating pragmas set on several lines, a state variable visibility is not set, a weak source of randomness and a control flow decision is made based on The block.timestamp environment variable. Avoid using any of those environment variables as sources of randomness and be aware that the use of these variables introduces a certain level of trust into miners.

AUDIT RESULT

Article	Category	Description	Result
Default Visibility	SWC-100 SWC-108	Functions and state variables visibility should be set explicitly. Visibility levels should be specified consciously.	PASS
Integer Overflow and Underflow	SWC-101	If unchecked math is used, all math operations should be safe from overflows and underflows.	PASS
Outdated Compiler Version	SWC-102	It is recommended to use a recent version of the Solidity compiler.	PASS
Floating Pragma	SWC-103	Contracts should be deployed with the same compiler version and flags that they have been tested thoroughly.	ISSUE FOUND
Unchecked Call Return Value	SWC-104	The return value of a message call should be checked.	PASS
Unprotected Ether Withdrawal	SWC-105	Due to missing or insufficient access controls, malicious parties can withdraw from the contract.	PASS
SELFDESTRUCT Instruction	SWC-106	The contract should not be self-destructible while it has funds belonging to users.	PASS
Reentrancy	SWC-107	Check effect interaction pattern should be followed if the code performs recursive call.	PASS
Uninitialized Storage Pointer	SWC-109	Uninitialized local storage variables can point to unexpected storage locations in the contract.	PASS
Assert Violation	SWC-110 SWC-123	Properly functioning code should never reach a failing assert statement.	PASS
Deprecated Solidity Functions	SWC-111	Deprecated built-in functions should never be used.	PASS
Delegate call to Untrusted Callee	SWC-112	Delegatecalls should only be allowed to trusted addresses.	PASS

DoS (Denial of Service)	SWC-113 SWC-128	Execution of the code should never be blocked by a specific contract state unless required.	PASS
Race Conditions	SWC-114	Race Conditions and Transactions Order Dependency should not be possible.	PASS
Authorization through tx.origin	SWC-115	tx.origin should not be used for authorization.	PASS
Block values as a proxy for time	SWC-116	Block numbers should not be used for time calculations.	ISSUE FOUND
Signature Unique ID	SWC-117 SWC-121 SWC-122	Signed messages should always have a unique id. A transaction hash should not be used as a unique id.	PASS
Incorrect Constructor Name	SWC-118	Constructors are special functions that are called only once during the contract creation.	PASS
Shadowing State Variable	SWC-119	State variables should not be shadowed.	PASS
Weak Sources of Randomness	SWC-120	Random values should never be generated from Chain Attributes or be predictable.	ISSUE FOUND
Write to Arbitrary Storage Location	SWC-124	The contract is responsible for ensuring that only authorized user or contract accounts may write to sensitive storage locations.	PASS
Incorrect Inheritance Order	SWC-125	When inheriting multiple contracts, especially if they have identical functions, a developer should carefully specify inheritance in the correct order. The rule of thumb is to inherit contracts from more /general/ to more /specific/.	PASS
Insufficient Gas Griefing	SWC-126	Insufficient gas griefing attacks can be performed on contracts which accept data and use it in a sub-call on another contract.	PASS
Arbitrary Jump Function	SWC-127	As Solidity doesnt support pointer arithmetics, it is impossible to change such variable to an arbitrary value.	PASS

Typographical Error	SWC-129	A typographical error can occur for example when the intent of a defined operation is to sum a number to a variable.	PASS
Override control character	SWC-130	Malicious actors can use the Right-To-Left-Override unicode character to force RTL text rendering and confuse users as to the real intent of a contract.	PASS
Unused variables	SWC-131 SWC-135	Unused variables are allowed in Solidity and they do not pose a direct security issue.	PASS
Unexpected Ether balance	SWC-132	Contracts can behave erroneously when they strictly assume a specific Ether balance.	PASS
Hash Collisions Variable	SWC-133	Using <code>abi.encodePacked()</code> with multiple variable length arguments can, in certain situations, lead to a hash collision.	PASS
Hardcoded gas amount	SWC-134	The <code>transfer()</code> and <code>send()</code> functions forward a fixed amount of 2300 gas.	PASS
Unencrypted Private Data	SWC-136	It is a common misconception that private type variables cannot be read.	PASS

SMART CONTRACT ANALYSIS

Started	Saturday May 08 2021 13:13:02 GMT+0000 (Coordinated Universal Time)
Finished	Sunday May 09 2021 13:41:55 GMT+0000 (Coordinated Universal Time)
Mode	Standard
Main Source File	LqdrToken.sol

Detected Issues

ID	Title	Severity	Status
SWC-103	A FLOATING PRAGMA IS SET.	low	acknowledged
SWC-103	A FLOATING PRAGMA IS SET.	low	acknowledged
SWC-103	A FLOATING PRAGMA IS SET.	low	acknowledged
SWC-103	A FLOATING PRAGMA IS SET.	low	acknowledged
SWC-103	A FLOATING PRAGMA IS SET.	low	acknowledged
SWC-116	A CONTROL FLOW DECISION IS MADE BASED ON THE BLOCK.TIMESTAMP ENVIRONMENT VARIABLE.	low	acknowledged
SWC-120	POTENTIAL USE OF "BLOCK.NUMBER" AS SOURCE OF RANDOMNESS.	low	acknowledged
SWC-120	POTENTIAL USE OF "BLOCK.NUMBER" AS SOURCE OF RANDOMNESS.	low	acknowledged
SWC-120	A CONTROL FLOW DECISION IS MADE BASED ON THE BLOCK.NUMBER ENVIRONMENT VARIABLE.	low	acknowledged

SWC-103 | A FLOATING PRAGMA IS SET.

LINE 8

low SEVERITY

The current pragma Solidity directive is "">=0.6.0<0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source File

- LqdrToken.sol

Locations

```
7
8  pragma solidity >=0.6.0 <0.8.0;
9
10 /*
11  * @dev Provides information about the current execution context, including the
12
```

SWC-103 | A FLOATING PRAGMA IS SET.

LINE 34

low SEVERITY

The current pragma Solidity directive is "">=0.6.0<0.8.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source File

- LqdrToken.sol

Locations

```
33
34 pragma solidity >=0.6.0 <0.8.0;
35
36 /**
37  * @dev Contract module which provides a basic access control mechanism, where
38
```

SWC-103 | A FLOATING PRAGMA IS SET.

LINE 102

low SEVERITY

The current pragma Solidity directive is "">=0.6.4"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source File

- LqdrToken.sol

Locations

```
101
102  pragma solidity >=0.6.4;
103
104  interface IBEP20 {
105    /**
106
```

SWC-103 | A FLOATING PRAGMA IS SET.

LINE 198

low SEVERITY

The current pragma Solidity directive is ""`>=0.6.0<0.8.0`"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source File

- LqdrToken.sol

Locations

```
197
198  pragma solidity >=0.6.0 <0.8.0;
199
200  /**
201   * @dev Wrappers over Solidity's arithmetic operations with added overflow
202
```

SWC-103 | A FLOATING PRAGMA IS SET.

LINE 359

low SEVERITY

The current pragma Solidity directive is "">=0.4.0"". It is recommended to specify a fixed compiler version to ensure that the bytecode produced does not vary between builds. This is especially important if you rely on bytecode-level verification of the code.

Source File

- LqdrToken.sol

Locations

```
358
359  pragma solidity >=0.4.0;
360
361
362
363
```

SWC-116 | A CONTROL FLOW DECISION IS MADE BASED ON THE BLOCK.TIMESTAMP ENVIRONMENT VARIABLE.

LINE 772

low SEVERITY

The block.timestamp environment variable is used to determine a control flow decision. Note that the values of variables like coinbase, gaslimit, block number and timestamp are predictable and can be manipulated by a malicious miner. Also keep in mind that attackers know hashes of earlier blocks. Don't use any of those environment variables as sources of randomness and be aware that use of these variables introduces a certain level of trust into miners.

Source File

- LqdrToken.sol

Locations

```
771 require(nonce == nonces[signatory]++, "LQDR::delegateBySig: invalid nonce");
772 require(now <= expiry, "LQDR::delegateBySig: signature expired");
773 return _delegate(signatory, delegatee);
774 }
775
776
```

SWC-120 | POTENTIAL USE OF "BLOCK.NUMBER" AS SOURCE OF RANDOMNESS.

LINE 802

low SEVERITY

The environment variable "block.number" looks like it might be used as a source of randomness. Note that the values of variables like coinbase, gaslimit, block number and timestamp are predictable and can be manipulated by a malicious miner. Also keep in mind that attackers know hashes of earlier blocks. Don't use any of those environment variables as sources of randomness and be aware that use of these variables introduces a certain level of trust into miners.

Source File

- LqdrToken.sol

Locations

```
801  {
802  require(blockNumber < block.number, "LQDR::getPriorVotes: not yet determined");
803
804  uint32 nCheckpoints = numCheckpoints[account];
805  if (nCheckpoints == 0) {
806
```


SWC-120 | POTENTIAL USE OF "BLOCK.NUMBER" AS SOURCE OF RANDOMNESS.

LINE 875

low SEVERITY

The environment variable "block.number" looks like it might be used as a source of randomness. Note that the values of variables like coinbase, gaslimit, block number and timestamp are predictable and can be manipulated by a malicious miner. Also keep in mind that attackers know hashes of earlier blocks. Don't use any of those environment variables as sources of randomness and be aware that use of these variables introduces a certain level of trust into miners.

Source File

- LqdrToken.sol

Locations

```
874  {
875  uint32 blockNumber = safe32(block.number, "LQDR::_writeCheckpoint: block number
exceeds 32 bits");
876
877  if (nCheckpoints > 0 && checkpoints[delegatee][nCheckpoints - 1].fromBlock ==
blockNumber) {
878  checkpoints[delegatee][nCheckpoints - 1].votes = newVotes;
879
```

SWC-120 | A CONTROL FLOW DECISION IS MADE BASED ON THE BLOCK.NUMBER ENVIRONMENT VARIABLE.

LINE 802

low SEVERITY

The block.number environment variable is used to determine a control flow decision. Note that the values of variables like coinbase, gaslimit, block number and timestamp are predictable and can be manipulated by a malicious miner. Also keep in mind that attackers know hashes of earlier blocks. Don't use any of those environment variables as sources of randomness and be aware that use of these variables introduces a certain level of trust into miners.

Source File

- LqdrToken.sol

Locations

```
801  {  
802  require(blockNumber < block.number, "LQDR::getPriorVotes: not yet determined");  
803  
804  uint32 nCheckpoints = numCheckpoints[account];  
805  if (nCheckpoints == 0) {  
806
```

DISCLAIMER

This report is subject to the terms and conditions (including without limitation, description of services, confidentiality, disclaimer and limitation of liability) set forth in the Services Agreement, or the scope of services, and terms and conditions provided to you (“Customer” or the “Company”) in connection with the Agreement. This report provided in connection with the Services set forth in the Agreement shall be used by the Company only to the extent permitted under the terms and conditions set forth in the Agreement. This report may not be transmitted, disclosed, referred to, or relied upon by any person for any purposes, nor may copies be delivered to any other person other than the Company, without Sysfixed’s prior written consent in each instance.

This report is not, nor should be considered, an “endorsement” or “disapproval” of any particular project or team. This report is not, nor should be considered, an indication of the economics or value of any “product” or “asset” created by any team or project that contracts Sysfixed to perform a security assessment. This report does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors, business, business model, or legal compliance.

This is a limited report on our findings based on our analysis, in accordance with good industry practice as of the date of this report, in relation to cybersecurity vulnerabilities and issues in the framework and algorithms based on smart contracts, the details of which are set out in this report. In order to get a full view of our analysis, it is crucial for you to read the full report. While we have done our best in conducting our analysis and producing this report, it is important to note that you should not rely on this report and cannot claim against us on the basis of what it says or doesn’t say, or how we produced it, and it is important for you to conduct your own independent investigations before making any decisions. We go into more detail on this in the below disclaimer below – please make sure to read it in full.

This report should not be used in any way to make decisions around investment or involvement with any particular project. This report in no way provides investment advice, nor should be leveraged as investment advice of any sort. This report represents an extensive assessing process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

This report is provided for information purposes only and on a non-reliance basis and does not constitute investment advice. No one shall have any right to rely on the report or its contents, and Sysfixed and its affiliates (including holding companies, shareholders, subsidiaries, employees, directors, officers, and other representatives) (Sysfixed) owe no duty of care.

ABOUT US

Sysfixed is a blockchain security certification organization established in 2021 with the objective to provide smart contract security services and verify their correctness in blockchain-based protocols. Sysfixed automatically scans for security vulnerabilities in Ethereum and other EVM-based blockchain smart contracts. Sysfixed a comprehensive range of analysis techniques—including static analysis, dynamic analysis, and symbolic execution—can accurately detect security vulnerabilities to provide an in-depth analysis report. With a vibrant ecosystem of world-class integration partners that amplify developer productivity, Sysfixed can be utilized in all phases of your project's lifecycle. Our team of security experts is dedicated to the research and improvement of our tools and techniques used to fortify your code.