

Nash Exchange Token
Smart Contract
Audit Report





TABLE OF CONTENTS

| Audited Details

- Audited Project
- Blockchain
- Addresses
- Project Website
- Codebase

Summary

- Contract Summary
- Audit Findings Summary
- Vulnerabilities Summary

Conclusion

| Audit Results

Smart Contract Analysis

- Detected Vulnerabilities
- Disclaimer
- About Us



AUDITED DETAILS

Audited Project

Project name	Token ticker	Blockchain
Nash Exchange Token	NEX	Polygon Matic

Addresses

Contract address	0xa486c6bc102f409180ccb8a94ba045d39f8fc7cb	
Contract deployer address	0x63ec5767F54F6943750A70eB6117EA2D9Ca77313	

Project Website

https://nash.io/

Codebase

https://polygonscan.com/address/0xa486c6bc102f409180ccb8a94ba045d39f8fc7cb#code



SUMMARY

Nash is a decentralized trading and payment platform. It utilizes an off-chain matching engine to enable faster and more complex trades than existing decentralized exchanges. By developing various innovative technologies, Nash aims to harness the power of blockchain while providing natural workflows for developers and an intuitive experience for users.

Contract Summary

Documentation Quality

Nash Exchange Token provides a very poor documentation with standard of solidity base code.

• The technical description is provided unclear and disorganized.

Code Quality

The Overall quality of the basecode is poor.

• Solidity basecode and rules are unclear and disorganized by Nash Exchange Token.

Test Coverage

Test coverage of the project is 100% (Through Codebase)

Audit Findings Summary

- SWC-110 SWC-123 | It is recommended to use of revert(), assert(), and require() in Solidity, and the new REVERT opcode in the EVM on lines 24.
- SWC-112 | Use delegatecall with caution and make sure to never call into untrusted contracts on lines 24.



CONCLUSION

We have audited the Nash Exchange Token project released in May 2021 to find issues and identify potential security vulnerabilities in the Nash Exchange Token project. This process is used to find technical issues and security loopholes that may be found in smart contracts.

The security audit report yielded unsatisfactory results, discovering high-risk and low-risk issues.

Writing a contract that does not follow the Solidity style guide can pose a significant risk. The serious and low problems we found in the smart contract are the contract delegates execution to another contract with a user-supplied address., and low-risk issue requirement violation. The smart contract delegates execution to a user-supplied address. This could allow an attacker to execute arbitrary code in the context of this contract account and manipulate the state of the contract account or execute actions on its behalf. A requirement was violated in a nested call, and the call was reverted. Ensure valid inputs are provided to the nested call (for instance, via passed arguments).

We were recommended to keep being aware of investing in this risky smart contract.



AUDIT RESULT

Article	Category	Description	Result	
Default Visibility	SWC-100 SWC-108	Functions and state variables visibility should be set explicitly. Visibility levels should be specified consciously.	PASS	
Integer Overflow and Underflow	SWC-101	If unchecked math is used, all math operations should be safe from overflows and underflows.	PASS	
Outdated Compiler Version	SWC-102	It is recommended to use a recent version of the Solidity compiler.	PASS	
Floating Pragma	SWC-103	Contracts should be deployed with the same compiler version and flags that they have been tested thoroughly.	PASS	
Unchecked Call Return Value	SWC-104	The return value of a message call should be checked.	pe PASS	
Unprotected Ether Withdrawal	SWC-105	Due to missing or insufficient access controls, malicious parties can withdraw from the contract.		
SELFDESTRUCT Instruction	SWC-106	The contract should not be self-destructible while it has funds belonging to users.		
Reentrancy	SWC-107	Check effect interaction pattern should be followed if the code performs recursive call.		
Uninitialized Storage Pointer	SWC-109	Uninitialized local storage variables can point to unexpected storage locations in the contract.	PASS	
Assert Violation	SWC-110 SWC-123	Properly functioning code should never reach a FOUNI		
Deprecated Solidity Functions	SWC-111	Deprecated built-in functions should never be used. PASS		
Delegate call to Untrusted Callee	SWC-112	Delegatecalls should only be allowed to trusted addresses.	ISSUE FOUND	



DoS (Denial of Service)	SWC-113 Execution of the code should never be blocked by a specific contract state unless required.		PASS
Race Conditions	Race Conditions SWC-114 Race Conditions and Transactions Order Dependency should not be possible.		PASS
Authorization through tx.origin	SWC-115	tx.origin should not be used for authorization.	
Block values as a proxy for time	SWC-116 Block numbers should not be used for time calculations.		PASS
Signature Unique ID	SWC-117 SWC-121 SWC-122	Signed messages should always have a unique id. A transaction hash should not be used as a unique id.	PASS
Incorrect Constructor Name	SWC-118		PASS
Shadowing State Variable	SWC-119 State variables should not be shadowed.		PASS
Weak Sources of Randomness	SWC-120	Random values should never be generated from Chain Attributes or be predictable.	
Write to Arbitrary Storage Location	SWC-124	The contract is responsible for ensuring that only authorized user or contract accounts may write to sensitive storage locations.	
Incorrect Inheritance Order When inheriting multiple contracts, especially if they have identical functions, a developer should carefully specify inheritance in the correct order. The rule of thumb is to inherit contracts from more /general/ to more /specific/.		PASS	
Insufficient Gas Griefing	SWC-126 contracts which accept data and use it in a sub-call on		PASS
Arbitrary Jump Function	SWC-127	As Solidity doesnt support pointer arithmetics, it is impossible to change such variable to an arbitrary value.	PASS



Typographical Error	SWC-129	A typographical error can occur for example when the intent of a defined operation is to sum a number to a variable.	
Override control character	SWC-130	Malicious actors can use the Right-To-Left-Override unicode character to force RTL text rendering and confuse users as to the real intent of a contract.	
Unused variables	SWC-131 SWC-135	Unused variables are allowed in Solidity and they do not pose a direct security issue.	
Unexpected Ether balance	SWC-132	Contracts can behave erroneously when they strictly assume a specific Ether balance.	
Hash Collisions Variable	SWC-133	Using abi.encodePacked() with multiple variable length arguments can, in certain situations, lead to a hash collision.	
Hardcoded gas amount	SWC-134	The transfer() and send() functions forward a fixed amount of 2300 gas.	
Unencrypted Private Data	SWC-136	It is a common misconception that private type variables cannot be read.	



SMART CONTRACT ANALYSIS

Started	Sunday May 09 2021 07:01:50 GMT+0000 (Coordinated Universal Time)		
Finished	Monday May 10 2021 06:00:03 GMT+0000 (Coordinated Universal Time)		
Mode	Standard		
Main Source File	UChildERC20Proxy.sol		

Detected Issues

ID		Title	Severity	Status
SW	/C-112	THE CONTRACT DELEGATES EXECUTION TO ANOTHER CONTRACT WITH A USER-SUPPLIED ADDRESS.	high	acknowledged
SW	/C-123	REQUIREMENT VIOLATION.	low	acknowledged



SWC-112 | THE CONTRACT DELEGATES EXECUTION TO ANOTHER CONTRACT WITH A USER-SUPPLIED ADDRESS.

LINE 24

high SEVERITY

The smart contract delegates execution to a user-supplied address. This could allow an attacker to execute arbitrary code in the context of this contract account and manipulate the state of the contract account or execute actions on its behalf.

Source File

- UChildERC20Proxy.sol

Locations

```
23 assembly {
24 let result := delegatecall(
25 sub(gas(), 10000),
26 _dst,
27 add(_calldata, 0x20),
28
```



SWC-123 | REQUIREMENT VIOLATION.

LINE 24

low SEVERITY

A requirement was violated in a nested call and the call was reverted as a result. Make sure valid inputs are provided to the nested call (for instance, via passed arguments).

Source File

- UChildERC20Proxy.sol

Locations

```
23 assembly {
24 let result := delegatecall(
25 sub(gas(), 10000),
26 _dst,
27 add(_calldata, 0x20),
28
```



DISCLAIMER

This report is subject to the terms and conditions (including without limitation, description of services, confidentiality, disclaimer and limitation of liability) set forth in the Services Agreement, or the scope of services, and terms and conditions provided to you ("Customer" or the "Company") in connection with the Agreement. This report provided in connection with the Services set forth in the Agreement shall be used by the Company only to the extent permitted under the terms and conditions set forth in the Agreement. This report may not be transmitted, disclosed, referred to, or relied upon by any person for any purposes, nor may copies be delivered to any other person other than the Company, without Sysfixed's prior written consent in each instance.

This report is not, nor should be considered, an "endorsement" or "disapproval" of any particular project or team. This report is not, nor should be considered, an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Sysfixed to perform a security assessment. This report does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors, business, business model, or legal compliance.

This is a limited report on our findings based on our analysis, in accordance with good industry practice as of the date of this report, in relation to cybersecurity vulnerabilities and issues in the framework and algorithms based on smart contracts, the details of which are set out in this report. In order to get a full view of our analysis, it is crucial for you to read the full report. While we have done our best in conducting our analysis and producing this report, it is important to note that you should not rely on this report and cannot claim against us on the basis of what it says or doesn't say, or how we produced it, and it is important for you to conduct your own independent investigations before making any decisions. We go into more detail on this in the below disclaimer below – please make sure to read it in full.

This report should not be used in any way to make decisions around investment or involvement with any particular project. This report in no way provides investment advice, nor should be leveraged as investment advice of any sort. This report represents an extensive assessing process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

This report is provided for information purposes only and on a non-reliance basis and does not constitute investment advice. No one shall have any right to rely on the report or its contents, and Sysfixed and its affiliates (including holding companies, shareholders, subsidiaries, employees, directors, officers, and other representatives) (Sysfixed) owe no duty of care.



ABOUT US

Sysfixed is a blockchain security certification organization established in 2021 with the objective to provide smart contract security services and verify their correctness in blockchain-based protocols. Sysfixed automatically scans for security vulnerabilities in Ethereum and other EVM-based blockchain smart contracts. Sysfixed a comprehensive range of analysis techniques—including static analysis, dynamic analysis, and symbolic execution—can accurately detect security vulnerabilities to provide an in-depth analysis report. With a vibrant ecosystem of world-class integration partners that amplify developer productivity, Sysfixed can be utilized in all phases of your project's lifecycle. Our team of security experts is dedicated to the research and improvement of our tools and techniques used to fortify your code.