

Unido Smart Contract Audit Report



03 Mar 2021



TABLE OF CONTENTS

Audited Details

- Audited Project
- Blockchain
- Addresses
- Project Website
- Codebase

Summary

- Contract Summary
- Audit Findings Summary
- Vulnerabilities Summary

Conclusion

Audit Results

Smart Contract Analysis

- Detected Vulnerabilities

Disclaimer

About Us



AUDITED DETAILS

Audited Project

Project name	Token ticker	Blockchain	
Unido	UDO	Ethereum	

Addresses

Contract address	0xea3983Fc6D0fbbC41fb6F6091f68F3e08894dC06	
Contract deployer address	0x203f58a7cf63d28b5E4271A30cB8E0e61A753F50	

Project Website

http://unido.us/

Codebase

https://etherscan.io/address/0xea3983Fc6D0fbbC41fb6F6091f68F3e08894dC06#code



SUMMARY

Unido is the enterprise gateway to DeFi and cryptocurrencies. Enables enterprises and institutional investors such as hedge funds, asset managers and digital banks to seamlessly manage and invest into DeFi and Crypto Markets.

Contract Summary

Documentation Quality

Unido provides a very good documentation with standard of solidity base code.

• The technical description is provided clearly and structured and also dont have any high risk issue.

Code Quality

The Overall quality of the basecode is standard.

• Standard solidity basecode and rules are already followed by Unido with the discovery of several low issues.

Test Coverage

Test coverage of the project is 100% (Through Codebase)

Audit Findings Summary

• SWC-110 SWC-123 | It is recommended to use of revert(), assert(), and require() in Solidity, and the new REVERT opcode in the EVM on lines 324 and 278.



CONCLUSION

We have audited the Unido project released on March 2021 to discover issues and identify potential security vulnerabilities in Unido Project. This process is used to find technical issues and security loopholes which might be found in the smart contract.

The security audit report provides a satisfactory result with some low-risk issues.

The issues found in the Unido smart contract code do not pose a considerable risk. The writing of the contract is close to the standard of writing contracts in general. The low-risk issues found are assertion violations triggered. Note that Solidity assert() statements should only be used to check invariants. Review the transaction trace generated for this issue and either make sure your program logic is correct, or use require() instead of assert() if your goal is to constrain user inputs or enforce preconditions. Remember to validate inputs from both callers (for instance, via passed arguments) and callees (for instance, via return values). It is recommended to use revert(), assert(), and require() in Solidity, and the new REVERT opcode in the EVM.



AUDIT RESULT

Article	Category	Description	Result	
Default Visibility	SWC-100 SWC-108	Functions and state variables visibility should be set explicitly. Visibility levels should be specified consciously.		
Integer Overflow and Underflow	SWC-101	If unchecked math is used, all math operations should be safe from overflows and underflows.	PASS	
Outdated Compiler Version	SWC-102	It is recommended to use a recent version of the Solidity compiler.	PASS	
Floating Pragma	SWC-103	Contracts should be deployed with the same compiler version and flags that they have been tested thoroughly.	PASS	
Unchecked Call Return Value	SWC-104	The return value of a message call should be checked.	PASS	
Unprotected Ether Withdrawal	SWC-105	Due to missing or insufficient access controls, malicious parties can withdraw from the contract.	PASS	
SELFDESTRUCT Instruction	SWC-106	The contract should not be self-destructible while it has funds belonging to users.	PASS	
Reentrancy	SWC-107	Check effect interaction pattern should be followed if the code performs recursive call.	ed PASS	
Uninitialized Storage Pointer	SWC-109	Uninitialized local storage variables can point to unexpected storage locations in the contract.	PASS	
Assert Violation	SWC-110 SWC-123	Properly functioning code should never reach a failing assert statement.	ISSUE FOUND	
Deprecated Solidity Functions	SWC-111	Deprecated built-in functions should never be used.	PASS	
Delegate call to Untrusted Callee	SWC-112	Delegatecalls should only be allowed to trusted addresses.	PASS	



DoS (Denial of Service)	SWC-113 SWC-128	Execution of the code should never be blocked by a specific contract state unless required.	PASS	
Race Conditions	SWC-114	Race Conditions and Transactions Order Dependency should not be possible.		
Authorization through tx.origin	SWC-115	tx.origin should not be used for authorization.	PASS	
Block values as a proxy for time	SWC-116	Block numbers should not be used for time calculations.		
Signature Unique ID	SWC-117 SWC-121 SWC-122	Signed messages should always have a unique id. A transaction hash should not be used as a unique id.	PASS	
Incorrect Constructor Name	SWC-118	Constructors are special functions that are called only once during the contract creation.	PASS	
Shadowing State Variable	SWC-119	State variables should not be shadowed.		
Weak Sources of Randomness	SWC-120	Random values should never be generated from Chain Attributes or be predictable.		
Write to Arbitrary Storage Location	SWC-124	The contract is responsible for ensuring that only authorized user or contract accounts may write to sensitive storage locations.	PASS	
Incorrect Inheritance Order	SWC-125	When inheriting multiple contracts, especially if they have identical functions, a developer should carefully specify inheritance in the correct order. The rule of thumb is to inherit contracts from more /general/ to more /specific/.		
Insufficient Gas Griefing	SWC-126	Insufficient gas griefing attacks can be performed on contracts which accept data and use it in a sub-call on another contract.		
Arbitrary Jump Function	SWC-127	As Solidity doesnt support pointer arithmetics, it is impossible to change such variable to an arbitrary value.	PASS	



Typographical Error	SWC-129	A typographical error can occur for example when the intent of a defined operation is to sum a number to a variable.	PASS
Override control character	SWC-130	Malicious actors can use the Right-To-Left-Override unicode character to force RTL text rendering and confuse users as to the real intent of a contract.	PASS
Unused variables	SWC-131 SWC-135	Unused variables are allowed in Solidity and they do not pose a direct security issue.	PASS
Unexpected Ether balance	SWC-132	Contracts can behave erroneously when they strictly assume a specific Ether balance.	PASS
Hash Collisions Variable	SWC-133	Using abi.encodePacked() with multiple variable length arguments can, in certain situations, lead to a hash collision.	PASS
Hardcoded gas amount	SWC-134	The transfer() and send() functions forward a fixed amount of 2300 gas.	
Unencrypted Private Data	SWC-136	It is a common misconception that private type variables cannot be read.	PASS



SMART CONTRACT ANALYSIS

Started	Tuesday Mar 02 2021 13:23:56 GMT+0000 (Coordinated Universal Time)
Finished	Wednesday Mar 03 2021 07:12:38 GMT+0000 (Coordinated Universal Time)
Mode	Standard
Main Source File	UnidoDistribution.sol

Detected Issues

ID	Title	Severity	Status
SWC-110	AN ASSERTION VIOLATION WAS TRIGGERED.	low	acknowledged
SWC-110	AN ASSERTION VIOLATION WAS TRIGGERED.	low	acknowledged



SWC-110 | AN ASSERTION VIOLATION WAS TRIGGERED.

LINE 324

Iow SEVERITY

It is possible to cause an assertion violation. Note that Solidity assert() statements should only be used to check invariants. Review the transaction trace generated for this issue and either make sure your program logic is correct, or use require() instead of assert() if your goal is to constrain user inputs or enforce preconditions. Remember to validate inputs from both callers (for instance, via passed arguments) and callees (for instance, via return values).

Source File

- UnidoDistribution.sol

Locations

```
323 function finalizeParticipants(POOL pool) external onlyOwner {
324 uint leftover = pools[pool];
325 pools[pool] = 0;
326 totalSupply = totalSupply.sub(leftover);
327 }
328
```





SWC-110 | AN ASSERTION VIOLATION WAS TRIGGERED.

LINE 278

Iow SEVERITY

It is possible to cause an assertion violation. Note that Solidity assert() statements should only be used to check invariants. Review the transaction trace generated for this issue and either make sure your program logic is correct, or use require() instead of assert() if your goal is to constrain user inputs or enforce preconditions. Remember to validate inputs from both callers (for instance, via passed arguments) and callees (for instance, via return values).

Source File

- UnidoDistribution.sol

Locations

277 function addParticipants(POOL pool, address[] calldata _participants, uint256[]
calldata _stakes) external onlyOwner {
278 require (pool >= POOL.SEED && pool <= POOL.RESERVE, "Must select a valid pool");
279 require (_participants.length == _stakes.length, "Must have equal array sizes");
280
281 uint lockoutPeriod;
282</pre>





DISCLAIMER

This report is subject to the terms and conditions (including without limitation, description of services, confidentiality, disclaimer and limitation of liability) set forth in the Services Agreement, or the scope of services, and terms and conditions provided to you ("Customer" or the "Company") in connection with the Agreement. This report provided in connection with the Services set forth in the Agreement shall be used by the Company only to the extent permitted under the terms and conditions set forth in the Agreement. This report may not be transmitted, disclosed, referred to, or relied upon by any person for any purposes, nor may copies be delivered to any other person other than the Company, without Sysfixed's prior written consent in each instance.

This report is not, nor should be considered, an "endorsement" or "disapproval" of any particular project or team. This report is not, nor should be considered, an indication of the economics or value of any "product" or "asset" created by any team or project that contracts Sysfixed to perform a security assessment. This report does not provide any warranty or guarantee regarding the absolute bug-free nature of the technology analyzed, nor do they provide any indication of the technologies proprietors, business, business model, or legal compliance.

This is a limited report on our findings based on our analysis, in accordance with good industry practice as of the date of this report, in relation to cybersecurity vulnerabilities and issues in the framework and algorithms based on smart contracts, the details of which are set out in this report. In order to get a full view of our analysis, it is crucial for you to read the full report. While we have done our best in conducting our analysis and producing this report, it is important to note that you should not rely on this report and cannot claim against us on the basis of what it says or doesn't say, or how we produced it, and it is important for you to conduct your own independent investigations before making any decisions. We go into more detail on this in the below disclaimer below – please make sure to read it in full.

This report should not be used in any way to make decisions around investment or involvement with any particular project. This report in no way provides investment advice, nor should be leveraged as investment advice of any sort. This report represents an extensive assessing process intending to help our customers increase the quality of their code while reducing the high level of risk presented by cryptographic tokens and blockchain technology.

This report is provided for information purposes only and on a non-reliance basis and does not constitute investment advice. No one shall have any right to rely on the report or its contents, and Sysfixed and its affiliates (including holding companies, shareholders, subsidiaries, employees, directors, officers, and other representatives) (Sysfixed) owe no duty of care.



ABOUT US

Sysfixed is a blockchain security certification organization established in 2021 with the objective to provide smart contract security services and verify their correctness in blockchain-based protocols. Sysfixed automatically scans for security vulnerabilities in Ethereum and other EVM-based blockchain smart contracts. Sysfixed a comprehensive range of analysis techniques—including static analysis, dynamic analysis, and symbolic execution—can accurately detect security vulnerabilities to provide an in-depth analysis report. With a vibrant ecosystem of world-class integration partners that amplify developer productivity, Sysfixed can be utilized in all phases of your project's lifecycle. Our team of security experts is dedicated to the research and improvement of our tools and techniques used to fortify your code.